



“Helping Australians clean less, live **more.**”

**CONTACT US**

(08) 8346 9600  
 sales@affordabletiles.com.au  
 www.affordabletiles.com.au

**Affordable Tiles**  
 94 – 96 Grange Road  
 Welland, South Australia

# NANO 4-WOODEN DECK



**Timber** – One of the most natural and sought after finishes for any home project. If left unprotected it can easily attract stains, mould and worse case causerotten timber. Protect your timber decking and other wooden furniture from mould and stains by a simple DIY Nano application. Cleaning and maintaining your timber surfaces just got easier.

**Where can I apply it?**

- Timber furniture (Indoor & Outdoor)
- Timber decking and fences
- Wooden benches
- Wooden structures
- Any wooden surfaces

**Why choose Nano4-Wooden Deck over other sealers?**

**Safer** – Our water-based, 100% natural eco-friendly formula reduces the health risks for Australian families when compared to other products on the market.

**Greener** – Our product is made of quartz sand also known as liquid glass. The natural ingredients are formulated with the environment in mind, therefore supporting efforts to make our planet a sustainable one.

**Smarter** – This sealer not only protects against stains and mould. It offers a full protection from water repellent, UV stable, moist, dirt particles, sea salt deposit and resistant to pressure wash (50 bar and below). Helping you making a smarter choice.

**Other features and benefits**

- Non-toxic
- Stain resistant
- Invisible coating
- Odourless
- Easy to clean
- Curing time 24 – 48 hours
- Protection up to 5 years
- Chemical resistant
- Frost resistant
- UV stable

PRODUCT SIZES	COVERAGE	EXAMPLE ITEMS TO SEAL AND PROTECT
500ml Bottle	2.5m <sup>2</sup> 16m <sup>2</sup>	Outdoor furniture, timber chairs and tables
1 Litre Bottle	5m <sup>2</sup> 33m <sup>2</sup>	Outdoor furniture, timber chairs and tables, timber decking and fences
4 Litre Bottle	2.5m <sup>2</sup> – 16m <sup>2</sup>	Timber decking and fences
20 Litre Drum	100m <sup>2</sup> 660m <sup>2</sup>	Timber decking and any large timber structures

SOFT TIMBER	COATS
Treated Pine, White Cypress, Plywood	2
HARD TIMBER	COATS
Merbau, Rosewood, Red Iron Bark, Spotted Gum, Karri, Jorrah, African Teak (Iroko)	4



UV Protection



Protect against salt water



Reduce moss & fungi growth



Long life protection



## EASY TO APPLY

**STEP 1.** We recommend doing a test on a small area first; allow it to cure for 24 – 48 hours to determine the desired results.

**STEP 2.** Before you apply, make sure the surface is clean, dry and free of residues.

Do not dilute **Nano4-Wooden Deck** with water, as it is not required.

**STEP 3.** You can use a brush, spray on or HVLP spray gun for best and economical installation.

For the best result apply generously on the surface and make sure it's wet. We recommend applying 2 to 4 coats (wet to wet). Apply the 2<sup>nd</sup> coat before the 1<sup>st</sup> coat dries while it's still wet (usually within 3 – 5 minutes).

**STEP 4.** **Nano4-Wooden Deck** takes about 48 hours (at 20°C) to be fully cured. The time required for curing may vary depending on ambient temperatures. Let it fully cure before allowing contact with water.

**Nano4-Wooden Deck** offers a long life protection of up to 5 years on new surface and when applied correctly according to instructions and maintained according to Nano4Life's maintenance guide. However, you may need to re-apply earlier depending on the harshness of the environment and on high foot traffic areas.

## TIPS

- For hard or denser timber like Merbau, Spotted Gum, African Teak etc. requires 4 thin coats (wet to wet). Apply each coat before the 1<sup>st</sup> coat dries while it's still wet (usually within 3 – 5 minutes). Full curing time is approximately 48 hours.
- When applying on large areas, divide into sections and complete each section at a time before moving onto the next, as application method needs to be applied wet to wet.
- If you're unsure please visit [www.nano4life.com.au](http://www.nano4life.com.au) for our application video or contact us.

## PRECAUTIONS – DO NOT SWALLOW

- Apply when surface temperature is between 5 – 30°C
- Avoid moisture contact with the surface after application until fully cured for 24 – 48 hours for optimum results
- Protect surrounding after application to avoid damage on freshly coated surface
- Wear gloves and protective clothing
- If using spray on, avoid applying in windy conditions
- Wash hands after application
- Store in a cool and dry location away from direct sunlight
- Keep out of reach of children
- PH Value 14 or above cleaner can destroy the effect
- **Nano4-Wooden Deck** does not protect against etching, wear and high water pressure 50 bar and above

## CHEMICAL COMPOSITION

Demineralised Water	(H <sub>2</sub> O)	90%
Silicon Dioxide	(Si <sub>2</sub> O)	10%

